# LED VAPOR TIGHT

The LED Vapor Tight fixture is ideally used as utility lighting in parking garages, stairwells, and harsh environments. Perfect for dry or wet location applications.

## DIMENSIONS

*Note: See *Product Specification* for exact dimensions.

26.3"/48.5"/50"

## CERTIFICATIONS

c(UL)us LISTED
E481307

FC

LED lighting facts
LED Product Partner

## FEATURES

- Stainless steel clips
- Optional 100% DR lens additive for impact resistance
- Built-in Constant Current LED Driver with High Efficient LED Module
- Suitable for ceiling mount or suspended mount
- Suitable for damp or dry environments
- Minimize labor and recycling costs
- Excellent light distribution and uniformity
- *Rated IP65*
- 5 Year Manufacturer's Warranty

## WARRANTY

## COMMON TECHNICAL DATA

| | |
|---|---|
| Color Temperature | 3000K-5000K |
| Beam Angle | 120º degrees |
| CRI | >80 |
| Operation Temperature | -30ºC to 40ºC |
| Lumen Efficiency | More than 135 LPW |
| Input Voltage | 100-277VAC |
| Frequency | 50-60Hz |
| Power Supply Efficiency | 90% |
| Rated Life | 50,000 hours |
| Power Factor | More than 0.99 |
| LED Type | SMT 2835 |
| Housing | Aluminum & Plastic |

This product has a warranty for a period of 5 years from the date of purchase. The warranty is invalid in the case of improper installation, tampering, or removal of the Q.C. date label. Installation in an improper working environment or installation not according to the current edition of the National Electric Code also invalidates the warranty. Should this product fail during the warranty period, it will be replaced free of charge, subject to correct installation and return of the faulty unit. James® does not accept responsibility for any installation costs associated with the replacement of this product. This warranty is in addition to the statutory rights in the country of purchase. James® reserves the right to alter specifications without prior notice.

# LED VAPOR TIGHT

## PRODUCT SPECIFICATION

| Product Number | Wattage | CCT | Lumens | Housing | Length x Width x Height |
|---|---|---|---|---|---|
| YB-STP8132-24W | 24W | 3000K-5000K | 3500 | Plastic | 50"x 4"x4.5" |
| YB-STP8232-48W | 48W | 3000K-5000K | 6830 | Plastic | 50"x 6.5"x 4.5" |
| YB-STP8332-72W | 72W | 3000K-5000K | 10200 | Plastic | 50"x10.5"x 4.5" |
| YB-STP8232-35W | 35W | 3000K-5000K | 4550 | Plastic | 50"x 6.5"x 4.5" |
| YB-STP8432-95W | 95W | 3000K-5000K | 13250 | Plastic | 50"x 17.4"x 4.5" |
| YB-STPA124-24W | 24W | 3000K-5000K | 3500 | Aluminum & Plastic | 48.5"x 3.4"x 2.8" |
| YB-STPA224-50W | 50W | 3000K-5000K | 6840 | Aluminum & Plastic | 48.5"x 4.1"x 3" |

## ORDERING GUIDE

| YB | STPA/STP | 8132-24W/8232-48W/8332-72W/8417-48W/8432-95W/124-24W/224-50W |
|---|---|---|
| Company Code | Housing Type | Wattage |

## MOUNTING OPTIONS



Stainless Steel Clip-on Brackets

## WIRING CONNECTION



L BLACK

N WHITE